Technical Data Sheet

Doc No-Ab/TDS/GLP-189

Rev No: 05 Date 02/2022-23

TECHNICAL DATA SHEET

Abdos Labtech Pvt. Ltd.

Slide Mailer, PP

Valid for Catalog No. P90107, P90108, P90109, P90110

1. Description/Specification

- **1.1 Description:** Slide Mailer, PP
- 1.1.1These slides Mailers are suitable for holding standard 25 x 75 mm slides.
- 1.1.2 They are ideal for secure shipping and storing of slides.
- 1.1.3 Easy to close secure snaps for storage of valuable slides.

1.2 Design:

Rectangular Slide Mailer design

1.3 Performance Specifications:

Code	Places	L x W x H (mm)	No. Per Case
P90107	1	85 x 42 x 5	25
P90108	2	82 x 70 x 5	25
P90109	3	100 x 84 x 5	25
P90110	5	82 x 30 x 17	25

1.4 Material:

- 1.4.1 PP- Polypropylene (PP), confirm US FDA 21CFR
- 1.4.2 Complies with the requirement of European Pharmacopoeia, Plastic Containers and closures for Pharmaceutical use.
- 1.4.3 The product has passed the USP testing including class VI tests, Materials has successful passed the biological tests according to ISO 10993 external communication devices for indirect blood contact for Prolonged period.
- 1.4.4 Free from Heavy metals, RoHS Free according to meets relevant requirements of EU regulations 1935/2004/CE ,2002/95/EC as amended, UE 10/2011 as amended. EU CONEG & it's following amendments. It is safe use in contact with food stuff, Pharmaceuticals & drinking water



Jasola, New Delhi - 110025

Technical Data Sheet

1.4.5 Product is manufactured without the use of Raw Materials of animal origin. Therefore BSE/TSE issue does not concern this product to the best of our Knowledge. No materials containing latex or natural rubber are used in the Manufacturing, handling & packaging process for this product.

1.5 Color: White

1.6 Quality control:

Product are manufactured, inspected and found to be in compliance with product & quality specification requirements as documented in ISO 9001:2015 & 13485:2016 Quality Management System. Testing of various characteristics in accordance with the valid specification, inspection reviewed & signed for product release amendments.

1.7 Other information

- 1.7.1 Impact resistant and tough.
- 1.7.2 Temperature range from -20°C to 120°C
- 1.7.3 Superior for its hardness, gloss, toughness, and electrical insulation properties.
- 1.8 Basic Features:
- 1.8.1 Autoclavability: Yes
- **1.8.2 Chemical resistance:** see website (<u>www.abdoslifesciences.com</u>)
- **1.8.3** Manufactured in Aseptic Environment

Autoclaving Guideline for Plastics

All plastic consumables are autoclavable at 121°C for 20 minutes, 15 psi/1atm. Do not use a dry cycle as this may cause deformation or weakening of the plastic. Allow temperature within the autoclave to return to at least 50°C before removing product.

Instruction for Use

Product can be used for food contact also.

Storage temp. Max 30°C

Before using the product check crackness etc.

Check all the information printed on pouches or boxes.

Always wear gloves while handling specimen.

WARNING

DO NOT store strong oxidizing agents.

Abdos Labtech Private Limited

DO NOT place any plastic labware in a flame.

DO NOT mix any chemicals that may result in a thermic reaction, which can cause product failure Consult local fire codes prior to storage of flammable liquids.



re

Ph. No: +91- (0) 1332235277

Technical Data Sheet







Abdos Labtech Private Limited (A Divison of Abdos Group) (An ISO 9001,13485,14001,18385,GMP & CE certified company) Shiv Ganga Industrial Estate Plot No-1, Lakheswari, Bhagwanpur, Roorkee-247667, (UK) INDIA

Registered office
13A Government
Place East, 2nd Floor Kolkata
West Bengal – 700069
CIN: U85100WB2008PTC123903
Corporate Office
319, 3rd Floor, DLF Tower A, DDA Dist. Centre
Jasola, New Delhi - 110025

Ph. No: +91- (0) 1332235277 Email:labtech@abdosindia.com Web: www.abdoslifesiences.com GST: 05AAGCA8605A1Z7