# **Technical Data Sheet**

Doc No Ab/TDS/CT-20

Rev No: 07 Date 04/2023-24

#### TECHNICAL DATA SHEET

Abdos Labtech Pvt. Ltd.

Swirl Maxi Micro Centrifuge

Valid for Catalog No. E11510

SRN (Single Registration Number): IN-MF-000022272

- 1. Description Specifications:
- 1.1 Description: Swirl Maxi Micro Centrifuge
- 1.1.1 Swirl Maxi is a personal micro centrifuge used for sedimentation of cells and virus, separation of sub-cellular organelles and isolation of macromolecules such as DNA, RNA, proteins or lipids.
- 1.1.2 Swirl Maxi is used in physical and chemical analysis, biochemistry, cellular biology, clinical labs, blood donation centre and high-end research.
- 1.1.3 Swirl Maxi has a large ergonomic design with easy to read display and sound. Both RPM and G-force can be displayed.
- 1.1.4 Swirl Maxi is stable and silent during operation. It also delivers fast acceleration and deceleration.
- 1.1.5 Swirl Maxi conforms to international safety standards and regulations. It has also passed the explosion proof test from CE, TUV and FCC. Swirl Maxi adapts a Brushless DC Motor.
- 1.1.6 Automatic lid-lock release prevents sample warming and allows easy access to samples.
- 1.1.7 The short spin function is used for quick spins by pressing and holding PULSE key. The centrifuge speed can be accelerated and held at the target speed.
- 1.1.8 High strength aluminium alloy rotors are fully autoclavable, and can withstand stream sterilizing at 121°C for 20 minutes.

#### 1.2 Design:

Swirl Maxi Micro Centrifuge

### 1.3 Performance Specifications:

**Abdos Labtech Private Limited** 

Specifications	E11510
Voltage	Single-phase, AC 220-240V
Frequency	50-60 Hz



### **Technical Data Sheet**

Current	3A
Max Speed	15000 rpm (500-15000rpm) with increment of 100 rpm
Max RCF	15100xg with increment of 100xg
Speed Accuracy	±20 rpm
Rotor Capacity	0.2ml, 0.5ml, 1.5ml & 2ml x 12 places.
Run Time	30sec-99min- HOLD (Continuous operation)
<b>Driving Motor</b>	Brushless DC Motor
Safety Devices	(i) Dual door interlock
	(ii) Over- speed detection
	(iii) Over temperature detection
	(iv) Automatic internal diagnosis
Noise Level	≤ 54 dB
Additional Features	(i) Speed/RCF switch
	(ii) Short-time run function
	(iii) Sound-alert function
Acceleration / Breaking time	11 sec for Acceleration & 9 sec for Breaking
Dimension	255x245x140 mm
Weight	6 kg
Permissible ambient Temp.	+4 to +40°C
Permissible ambient Humidity	80%

**1.4 Material:** ABS (Acrylonitrile Butadiene Styrene)

**1.5 Color:** Grey & White

**1.6 E11510** – Swirl Maxi Micro Centrifuge, CE certified. Swirl Maxi Micro Centrifuge with 12 Place Rotor for 0.2, 0.5, 1.5 & 2.0 ml **- 1No./case** 

### 1.7 Spare Accessories

- 1.7.1 **E11511** 12 Place Rotors for 0.2, 0.5, 1.5 & 2.0ml **1No./case**
- 1.7.2 **E11512** Rotor Adaptor for 0.2ml -2ml used with E11511 **24No./case**
- 1.7.3 **E11513 -** Rotor Adaptor for 0.5ml -2ml used with E11511 **24No./case**

Warranty: 12 months from the date of Installation or 15 months from the date of Invoicing.



Ph. No: +91- (0) 1332235277 Email:labtech@abdosindia.com Web: www.abdoslifesiences.com GST: 05AAGCA8605A1Z7

# **Technical Data Sheet**

### **Instruction for Use**

Storage temp. Max 30°C

Before using the product check.

Check all the information printed on pouches or boxes.

Always wear gloves while handling specimen.

### **WARNING**

**DO NOT** store strong oxidizing agents.

**DO NOT** place any plastic labware in a flame.

**DO NOT** mix any chemicals that may result in a thermic reaction, which can cause product failure Consult local fire codes prior to storage of flammable liquids.





Abdos Labtech Pvt. Ltd.

Plot No. 1 Lakeshwari Bhagwanpur Roorkee 247667 (UK) India Email: labtech@abdosindia.com, www.abdoslifesciences.com Ph: +(91) 11 41081897





**Quality Manager** Abdos Labtech Private Limited **Employee Code 30110** 



**Abdos Labtech Private Limited** 

