

TECHNICAL DATA SHEET

Doc No – Ab/TDS/BC-150 Rev No: 07 Date- 05/2024-25

Abdos Labtech Pvt. Ltd.
Heavy Duty Wide Mouth Carboy with Stopcock, HDPE

Valid for Catalog No. P11511, P11512, P11513, P11510

SRN (Single Registration Number): IN-MF-000022272

1. Description/Specification

- **1.1 Description:** Heavy Duty Wide Mouth Carboy with Stopcock, HDPE
- 1.1.1 Abdos Carboys are manufactured using high purity virgin USP Class VI Medical grade High Density poly Ethylene (HDPE).
- 1.1.2 These carboys come with secure sealing cap for better security and long-term storage.
- 1.1.3 These carboys are used for storing and shipping reagents, chemicals, culture media, and standards.
- 1.1.4 These heavy-duty carboys are large with wide mouth capable of handling large volume.
- 1.1.5 These are very strong and durable for extended use over time with a strong carrying handle on both sides of the carboy.
- 1.1.6 Comes with high quality and durable stopcock or tap for easy withdrawal of liquids, chemicals, reagents, culture media and standards.
- 1.1.7 Superior chemical resistance.

1.2 Raw material:

1.2.1 Body: HDPE (High Density poly Ethylene)

1.2.2 Cap: PP (Polypropylene)

1.3 Material:

- 1.3.1 High Density poly Ethylene (HDPE), Hydrophobic, confirm US FDA 21CFR
- 1.3.2 The product complies with USP class VI. Free from Heavy metals, it is safe to use in contact with food stuff, Pharmaceuticals & drinking water.
- 1.3.3 Product is manufactured without the use of Raw Materials of animal origin. Therefore BSE/TSE issue does not concern this product to the best of our knowledge. No materials

Lic. No.: MFG/IVD/2024/000158 & MFG/MD/2024/000898



TECHNICAL DATA SHEET

Doc No – Ab/TDS/BC-150 Rev No: 07 Date- 05/2024-25

Abdos Labtech Pvt. Ltd. Heavy Duty Wide Mouth Carboy with Stopcock, HDPE

containing latex or natural rubber are used in the Manufacturing, handling & packaging process for this product.

1.4 Quality Control:

- 1.4.1 Product are manufactured, inspected and found to be in compliance with product & quality specification requirements as documented in ISO 9001:2015 & 13485:2016 Quality Management System. Testing of various characteristics in accordance with the valid specification, inspection reviewed & signed for product release.
- 1.4.2 Can be used at a temperature below 0°C.

1.5 DIMENSIONAL SPECIFICATIONS:

Code	Capacity (lts)	Mouth Diameter (mm)	Height (mm)	No. per Case
P11511	30	250	440	1
P11512	50	250	650	1
P11513	100	250	800	1
P11510	Spare Stopcock	9	NA	1

1.6 GENERAL FEATURES:

CE	Yes
Autoclavability	No
Translucence	Yes
Resistant	To be effected by radiations
Sterilization	NA
Temperature	From -40° C to $+80^{\circ}$ C



Ph. No: +91- (0) 1332235277

Email:labtech@abdosindia.com

Web: www.abdoslifesiences.com

TECHNICAL DATA SHEET

Doc No – Ab/TDS/BC-150 Rev No: 07 Date- 05/2024-25

Abdos Labtech Pvt. Ltd. Heavy Duty Wide Mouth Carboy with Stopcock, HDPE

Leak Proof	Yes

- 1.7 Chemical resistance: See website (www.abdoslifesciences.com)
- **1.7.1** Manufactured in Aseptic Environment
- 1.7.2 **Intended use:** Widely used in scientific studies of molecular biology, clinical chemistry, biochemistry and any type of scientific laboratory.
- 1.8 Other Information (not applicable if neglected):
- **1.8.1 Fair resistance**; exposure (30 days) to the chemical does not cause any damage.
- **1.8.2 Sufficient resistance;** exposure causes damage of poor importance, which sometimes is only temporary.
- **1.8.3 Poor resistance**; exposure to chemicals is not allowed or causes immediate permanent damage.

Results of testing with reference materials are to be considered as indication: in case of specific use, it is recommended to carry out preliminary testing.

Information relating to the resistance of plastic materials to temperatures, sterilization and washing treatments, have been made as per reports of the raw materials' producers, following the data published in the literature and the experience gained in the use of products.

WARNING

DO NOT store strong oxidizing agents.

DO NOT place any plastic labware in a flame.

DO NOT mix any chemicals that may result in a thermic reaction, which can cause product failure

Consult local fire codes prior to storage of flammable liquids in carboys/bottles/aspirators. Consult OSHA guidelines prior to handling or lifting filled carboys/bottles/aspirators.



TECHNICAL DATA SHEET

Doc No – Ab/TDS/BC-150 Rev No: 07 Date- 05/2024-25

Abdos Labtech Pvt. Ltd. Heavy Duty Wide Mouth Carboy with Stopcock, HDPE

If applicable: Using the spigot as a handle can ruin the threads and cause the spigot not to seal properly.

Cleaning:

Bottles/Aspirators/Carboys need to be cleaned by hand using a non-abrasive, neutral pH, mild detergent that does not contain a sheeting agent.

Cap and Spigot Cleaning: (if applicable)

- 1. Remove O-ring from cap.
- 2. Disassemble the spigot.
- 3. Spray and wipe the spigot, cap and O-ring with 70% Isopropyl Alcohol.
- 4. Rinse all parts with distilled water.
- 5. Replace O-ring in cap.
- 6. Autoclave cap and spigot at 121°C at 15 psi for 20 minutes.

Instruction for Use

Product can be used for food contact also.

Storage temp. Max 30°C

Before using the product check crackness, pouch punctured etc.

Check all the information printed on pouches or boxes.

Always wear gloves while handling specimens.

Ph. No: +91- (0) 1332235277 Email:labtech@abdosindia.com Web: www.abdoslifesiences.com



Ph. No: +91- (0) 1332235277


Email:labtech@abdosindia.com

Web: www.abdoslifesiences.com

TECHNICAL DATA SHEET

Doc No – Ab/TDS/BC-150 Rev No: 07 Date- 05/2024-25

Abdos Labtech Pvt. Ltd. Heavy Duty Wide Mouth Carboy with Stopcock, HDPE







Ph. No: +91- (0) 1332235277

Email:labtech@abdosindia.com

Web: www.abdoslifesiences.com

TECHNICAL DATA SHEET

Doc No – Ab/TDS/BC-150 Rev No: 07 Date- 05/2024-25

Abdos Labtech Pvt. Ltd. Heavy Duty Wide Mouth Carboy with Stopcock, HDPE

