

TECHNICAL DATA SHEET

Doc No – Ab/TDS/ GLP-176 Rev No: 04 Date- 05/2024-25

Abdos Labtech Pvt. Ltd. Utility Tray, PP

Valid for Catalog No. P90115, P90116

SRN (Single Registration Number): IN-MF-000022272

1. Description/Specification

1.1 Description: Utility Tray, PP

- 1.1.1 Moulded from high quality virgin Polypropylene to ensure excellent results.
- 1.1.2 These Utility Trays are used for routine washing and keeping labware and Transporting material.
- 1.1.3This tray is designed for easy grip and handling heavy loads.

1.2 Design: Tray

1.3 Performance Specifications:

Code	LxWxH (mm)	No. per Case
P90115	350x275x75	10
P90116	360x310x130	6

1.4 Material:

- 1.4.1 PP- Polypropylene (PP), confirm US FDA 21CFR
- 1.4.2 Free from Heavy metals, It is safe use in contact with food stuff, Pharmaceuticals & drinking water
- 1.4.3 Product is manufactured without the use of Raw Materials of animal origin. Therefore BSE/TSE issue does not concern this product to the best of our knowledge. No materials containing latex or natural rubber are used in the Manufacturing, handling & packaging process for this product.

Lic. No.: MFG/IVD/2024/000158 & MFG/MD/2024/000898

Ph. No: +91- (0) 1332235277 Email:labtech@abdosindia.com Web: www.abdoslifesiences.com



TECHNICAL DATA SHEET

Doc No – Ab/TDS/ GLP-176 Rev No: 04 Date- 05/2024-25

Abdos Labtech Pvt. Ltd. Utility Tray, PP

1.5 Color: Translucent

1.6 Quality control: Products are manufactured, inspected and found to be in compliance with product & quality specification requirements as documented in ISO 9001:2015 & 13485:2016 Quality Management System. Testing of various characteristics in accordance with the valid specification, inspection reviewed & signed for product release amendments.

1.7 Basic Features

1.7.1 Made up of High pure virgin Polypropylene (PP)

1.7.2 Temperature range: -80° C to $+121^{\circ}$ C

1.7.3 Autoclavability: Yes, Autoclavable at 15 psi and 121°C for 20 minutes

1.7.4 Chemical resistance: See website (www.abdoslifesciences.com)

1.7.5 Manufactured in Aseptic Environment

1.7.6 Intended use: Widely used in scientific studies of molecular biology, clinical chemistry, biochemistry and any type of scientific laboratory.

Autoclaving Guideline for Plastics

All plastic consumables are autoclavable at 121°C for 20 minutes, 15 psi/1atm. Do not use a dry cycle as this may cause deformation or weakening of the plastic. Allow temperature within the autoclave to return to at least 50°C before removing product.

Instruction for Use

Product can be used for food contact also. Storage temp. Max 30°C Before using the product check crackness etc. Check all the information printed on pouches or boxes.

Always wear gloves while handling specimens.



Ph. No: +91- (0) 1332235277

Email:labtech@abdosindia.com

Web: www.abdoslifesiences.com

TECHNICAL DATA SHEET

Doc No – Ab/TDS/ GLP-176 Rev No: 04 Date- 05/2024-25

Abdos Labtech Pvt. Ltd. Utility Tray, PP


WARNING

DO NOT store strong oxidizing agents.

DO NOT place any plastic labware in a flame.

DO NOT mix any chemicals that may result in a thermic reaction, which can cause product failure

Consult local fire codes prior to storage of flammable liquids.



Quality Manager
Abdos Labtech Private Limited
Employee Code 30110



Ph. No: +91- (0) 1332235277

Email:labtech@abdosindia.com

Web: www.abdoslifesiences.com

TECHNICAL DATA SHEET

Doc No – Ab/TDS/ GLP-176 Rev No: 04 Date- 05/2024-25

Abdos Labtech Pvt. Ltd. Utility Tray, PP

