

Technical Data Sheet

Doc No–Ab/TDS/UTL-229

Rev No: 05 Date 02/2022-23

TECHNICAL DATA SHEET

Abdos Labtech Pvt. Ltd.

Hi/Lo Temperature Tape

Valid for Catalog No. U20603

1. Description/Specification

1.1 Description: Hi/Lo Temperature Tape

1.1.1 These autoclavable tapes adhere to almost any dry surface-glass, plastic, metal, paper and rubber.

1.1.2 These are cloth textured tape that can stick to any surface or shape and can with stands acid, alkalis, oils and greases, dry ice and liquid gases wont crack or peel in dry oven or cryogenic temperatures.

1.2 Design: Hi/Lo Temperature Tape

1.3 Performance Specifications:

Code	Size (Inch)	No. Per Case
U20603	1	1 Roll

1.4 Color: White

1.5 Quality control:

Product are manufactured, inspected and found to be in compliance with product & quality specification requirements as documented in ISO 9001:2015 & 13485:2016 Quality Management System. Testing of various characteristics in accordance with the valid specification, inspection reviewed & signed for product release.

1.6 Other information:

1.6.1 **Chemical resistance:** See website (www.abdoslifesciences.com)

1.6.2 Manufactured in Aseptic Environment

Instruction for Use

Storage temp. Max 30°C

Before using the product check crackness etc.

Check all the information printed on pouches or boxes.

Always wear gloves while handling specimen.



Abdos Labtech Private Limited
(A Division of Abdos Group)
(An ISO 9001,13485,14001,18385,GMP & CE certified company)
Shiv Ganga Industrial Estate
Plot No-1, Lakheswari, Bhagwanpur,
Roorkee-247667, (UK) INDIA

Registered office
13A Government
Place East, 2nd Floor Kolkata
West Bengal – 700069
CIN: U85100WB2008PTC123903
Corporate Office
319, 3rd Floor, DLF Tower A, DDA Dist. Centre
Jasola, New Delhi - 110025

Ph. No: +91- (0) 1332235277
Email:labtech@abdosindia.com
Web: www.abdoslifesciences.com
GST: 05AAGCA8605A1Z7

Technical Data Sheet

WARNING

DO NOT store strong oxidizing agents.

DO NOT place any plastic labware in a flame.

DO NOT mix any chemicals that may result in a thermic reaction, which can cause product failure

Consult local fire codes prior to storage of flammable liquids.

